

VRP

Model

9000-0339

13.0 A
9000 VA
9000 W
230/400 V

15000-0339

21.7 A
15000 VA
15000 W
230/400 V

22500-0339

32.6 A
22500 VA
22500 W
230/400 V

30000-0339

43.5 A
30000 VA
30000 W
230/400 V

45000-0339

65.2 A
45000 VA
45000 W
230/400 V

Fail-safe

Automatic voltage regulator

PWM precision

Precision PWM Automatic Voltage Regulator

The VRP three-phase automatic precision AC voltage regulator allows trouble-free operation of electronic equipment over a very wide mains voltage range of 160-300 V found in many countries. TSi Power's VRP series is designed to provide precisely regulated power with a typical response time of 20 ms.

Typical VRP applications

The VRP is designed for applications where absolutely safe and precisely regulated AC power is required, such as base transceiver stations (BTS), backhaul transmission sites (including microwave links), radio/tv broadcast transmitters, industrial process controllers (PLCs), inspection equipment, CNC machines and laboratory or analytical measurement equipment.

How the VRP works


The high frequency insulated gate bi-polar transistor (IGBT) driven converter takes the incoming AC power, measures it against the nominal voltage reference and adds or subtracts voltage to achieve a precisely regulated 230 V output. The automatic bypass will be activated when there is a fault condition. Green LEDs are used to indicate Normal (regulating mode) operation.



Top view showing the Internal components

Features and Benefits

- Since the VRP does not switch components in the power path, it is compatible with most loads.
- Automatic bypass circuitry assures failsafe operation.
- Output voltage to within $\pm 3\%$ is provided for superior regulation.
- Includes a two-year limited warranty.
- AC input/output DIN type wiring terminals facilitate wiring connections.
- Internal surge voltage protection assures trouble-free operation.
- AC input circuit breakers and load over current protection prevent costly equipment damage.
- Circuit board assemblies are connectorized for easy replacement.
- Display circuit board monitors each phase independently and displays operational status by means of colored LEDs.

**TSi POWER**1103 W Pierce Avenue
Antigo, WI 54409 USA

Tel: + 1-715-623-0636


Fax: + 1-715-623-2426

Toll-Free: 1-800-874-3160

email: sales@tsipower.com

Web: www.tsipower.com

SPECIFICATION	VRP-9000	VRP-15000	VRP-22500	VRP-30000	VRP-45000
ELECTRICAL					
Capacity VA & Watts	9000	15000	22500	30000	45000
Switching Technology	High frequency 20 kHz IGBT AC chopper/inverter				
INPUT					
Voltage	Normal - 230 V, Input range - 160 to 330 V, regulation range - 184 to 276 V, three-phase wye				
Frequency	60 Hz ± 5 %				
Current Amps per phase	13.6 A @ 230 V	22.6 A @ 230 V	32.6 A @ 230 V	45.3 A @ 230 V	67.9 A @ 230 V
Current Amps @ full load	17 A @ 184 V	28.3 A @ 184 V	40.8 A @ 184 V	56.6 A @ 184 V	84.9 A @ 184 V
Circuit breaker rating	3 x 20 A	3 x 30 A	3 x 40 A	3 x 50 A	3 x 80 A
Input wire size	4 mm ² - AWG 12	6 mm ² - AWG 10	8 mm ² - AWG 8	13 mm ² - AWG 6	33 mm ² - AWG 2
OUTPUT					
Voltage	230/400 V ± 3 % (184 - 264 V / L-N input)				
Output power	9000 VA/W	15000 VA/W	22500 VA/W	30000 VA/W	45000 VA/W
Current Amps per phase	13.0 A	21.7 A	32.6 A	43.5 A	65.2 A
Overload protection	Circuit Breaker	Circuit Breaker	Circuit Breaker	Electronic	Electronic
Automatic bypass	Transfers to unregulated AC in case of failure				
Harmonic distortion	Sinusoidal, <5 % THD				
Power efficiency @ 230 V nominal	98 %				
Power efficiency in max boost mode	96 %				
System status indicators	Green LED ON-Normal operation - Amber LED ON-Bypass operation - Red LED ON-Fault				
Surge voltage let-through, 1.2 μs x 50 μs, 6 kV, 8 x 20 μs, 3 kA waveform	Line - Neutral < 300 V				
PHYSICAL					
Dimensions	22.5" (57 cm) High x 24" (61 cm) Wide x 24" (61 cm) Deep				
Weight lbs (kg)	170 (77)	200 (91)	240 (109)	300 (136)	335 (152)
SAFETY					
Standards	Designed to comply with IEC 60950-1 standards. Protection class IP 20				
ENVIRONMENTAL					
Ambient temperature	0° C to 40° C; Cooling method: Forced Air; Humidity: 0 - 95 % Non-condensing				
WARRANTY					
Warranty	Two-year limited warranty, parts and labor				



TSi POWER

1103 W Pierce Avenue
Antigo, WI 54409 USA

Tel: + 1-715-623-0636
Fax: + 1-715-623-2426
Toll-Free: 1-800-874-3160
email: sales@tsipower.com
Web: www.tsipower.com

TSi Power's ongoing product improvement process makes specifications subject to change. Other companies product names herein are for identification purposes only and may be trademarks of their respective companies.

VRP system (per phase)

